

LAW OFFICES
SUGHRUE, MION, ZINN, MACPEAK & SEAS, PLLC

2100 PENNSYLVANIA AVENUE, N.W.
WASHINGTON, D.C. 20037-3202
TELEPHONE (202) 293-7060
FACSIMILE (202) 293-7860

JAPAN OFFICE

TOEI NISHI SHIMBASHI BLDG. 4F
13-5 NISHI SHIMBASHI 1-CHOME
MINATO-KU, TOKYO 105, JAPAN
TELEPHONE (03) 3503-3760
FACSIMILE (03) 3503-3756

September 13, 2000

1c715 U.S. PTO
09/13/00
CALIFORNIA OFFICE
1000 CAMINO REAL
MENLO PARK, CA 94025
TELEPHONE (650) 325-5800
FACSIMILE (650) 325-6606

BOX: PATENT APPLICATION

Assistant Commissioner for Patents
Washington, D.C. 20231

Re: Application of Eiiji TERAUE
**COLOR CONVERSION METHOD, COLOR CONVERSION APPARATUS AND COLOR CONVERSION
DEFINITION STORAGE MEDIUM**
Our Reference: Q60758

Dear Sir:

Attached hereto is the application identified above including the specification, claims, executed Declaration and Power of Attorney, twelve (12) sheets of drawings, one (1) priority document, Information Disclosure Statement, PTO Form 1449 with reference, executed Assignment and PTO Form 1595.

The Government filing fee is calculated as follows:

Total Claims	9 - 20 =	0 x \$18 =	\$ 000.00
Independent Claims	3 - 3 =	0 x \$78 =	\$ 000.00
Base Filing Fee	(\$690.00)		\$ 690.00
Multiple Dep. Claim Fee	(\$260.00)		\$ 000.00
TOTAL FILING FEE			\$ 690.00
Recordation of Assignment Fee			\$ 40.00
TOTAL U.S. GOVERNMENT FEE			\$ 730.00

Checks for the statutory filing fee of \$ 690.00 and Assignment recordation fee of \$ 40.00 are attached. You are also directed and authorized to charge or credit any difference or overpayment to Deposit Account No. 19-4880. The Commissioner is hereby authorized to charge any fees under 37 C.F.R. 1.16 and 1.17 and any petitions for extension of time under 37 C.F.R. 1.136 which may be required during the entire pendency of the application to Deposit Account No. 19-4880. A duplicate copy of this transmittal letter is attached.

Priority is claimed from:

Japanese Patent Application

Filing Date

Hei. 11-259831

September 14, 1999

Respectfully submitted,
SUGHRUE, MION, ZINN, MACPEAK & SEAS
Attorneys for Applicant(s)

By Darryl Mexic
Darryl Mexic
Registration No. 23,063

DM:slb

SPECIFICATION

COLOR CONVERSION METHOD, COLOR CONVERSION APPATATUS AND COLOR CONVERSION DEFINITION STORAGE MEDIUM

5

BACKGROUND OF THE INVENTION

Field of the Invention

The present invention relates to a color
conversion method of converting image data for printing to
10 image data for a proofer, a color conversion apparatus and
a color conversion definition storage medium for storing
therein a color conversion definition to perform such a
color conversion, which are applied to a system wherein
when a color printing is performed by a color printing
15 machine using a spot color ink as well as a process color
ink, a proofer such as a printer or a CRT display unit is
used to output a proof image representing a color of a
color printed matter (including print-out and image
display).

20 Description of the Related Art

Hitherto, in the event that a color printing
machine is used to perform a color image printing, before
the printing is performed, a proof image, which is similar
in color to the utmost to the same color as a color of an
25 image printed by the color printing machine, is printed out
using a color printer and the like, or alternatively
displayed on a screen of a color display unit. In the

event that such a proof image is produced, there are detected a print profile describing a relation between image data and colors of actual printing matters, which print profile is associated with a type of a printing machine for the intended printing and using conditions of the printing machine (conditions necessary for some printing, including a sort of ink to be used and a quality of a printing paper; and a type of a printing machine, are referred to as printing conditions), and a proofer profile describing a relation between image data and colors of actually outputted proof images, which proofer profile is associated with a type of a proofer outputting proof images and using conditions of the proofer (conditions necessary for outputting of some proof image, including a type of a proofer, are referred to as proof conditions), and then the image data for printing is converted to the image data for the proofer in accordance with the print profile and the proofer profile, so that a proof image is outputted in accordance with the converted image data for the proofer. Thus, it is possible to obtain the proof image coincides with the actual printing matter in color. Usually, the print profile associated with the typical printing conditions is offered from a printer (a printing service trader), and the proofer profile is also offered, with respect to printers (devices) for the purpose of a proof image output, from a maker of the printers.

In the event that the image data for printing is

converted into the image data for a proofer to output the proof image, usually, the print profile and the proofer profile are combined to produce a LUT (Look Up Table), and the LUT is referred to and regarding a low order bit side
5 on which the LUT fails to describe the association, an interpolation arithmetic operation is performed, so that the image data for printing is converted into the image data for the proofer.

Here, a printing is performed usually using
10 process color ink of four colors of CMYK, but in some case it happens that spot color ink is used in addition to the process color ink of those four colors. In this case, it is not realistic that there is prepared a print profile on the combination of the process color ink of four colors
15 of CMYK and the various sorts of spot color ink in its entirety, and usually, there is prepared a print profile related to the printing using the process color ink of four colors of CMYK. Accordingly, the LUT thus produced is an LUT in which process color image data defined by color
20 spaces of four colors of CMYK wherein the process color ink of four colors of CMYK is used to perform printing is converted into image data defined by color spaces of three colors of RGB wherein color materials of, for example, three colors of RGB is used to output a proof
25 image for proofer.

In the situation as mentioned above, when the printing is performed using the spot color ink as well as

the process color ink of four colors of CMYK, it is a problem as to how the proof image of the printed matter is outputted.

Usually, a printer for a proof image output is of a type of outputting an image through for example, color materials of three colors of RGB or color materials of four colors of CMYK, and it is extremely rare that spot color materials coincident with spot colors intended for use of the printing are prepared. Further, also in the event that a proof image is displayed on a CRT display unit, there is no way other than all the colors being represented by a combination of three colors of RGB. Thus, the printed matter including the spot color will be represented by three colors of RGB in its entirety.

In this case, according to the earlier technology, there is adopted a method in which spot color image data is converted into process color image data of four colors of CMYK in accordance with characteristics (coordinates values on the $L^*a^*b^*$ space and the like) of characteristic ink to be used for intended printing, which is available from a maker of the characteristic ink, and image data (dot % data and the like) for spot color for printing, the process color image data for spot color and the process color image data for process color ink of four colors of CMYK except the spot color are combined, and the combined process color image data of four colors of CMYK is converted by the conversion system such as the LUT into,

for example, image data of three colors of RGB, for a proofer, so that a proof image is outputted based on the image data for the proofer thus converted. In this case, the spot color is separated into four colors of CMYK, and is converted into the image data for the proofer by the conversion system comprising the LUT as mentioned above for the process color. Thus, this is a problem in accuracy of color reproduction of the spot color.

In Japanese Patent Application Laid Open Gazette Hei. 10-248017, there is proposed a technology in which accuracy of color reproduction of the spot color is improved. According to the technology, of the printing image data, the process color image data of four colors of CMYK is converted into process color image data for a proofer by a first conversion system comprising the LUT as mentioned above, and on the other hand, as to a spot color, there is prepared a second conversion system adapted for the spot color, and image data for the spot color is converted into image data for the proofer by the second conversion system. Both the image data converted by the first and second conversion systems are combined on a color space (e.g. RGB color space) for the proofer.

According to such a technology, as compared with the above-mentioned earlier developed technology in which the spot color is separated and is converted by the conversion system which is not prepared as one for a spot color, there is prepared a second conversion system adapted

for the spot color as well as a first conversion system adapted for the process color ink of four colors of CMYK. Thus, it is possible to perform a color conversion with greater accuracy as to the spot color and thereby improving the color reproduction accuracy of the spot color.

Now let us consider a case where there is constructed such a system that various types of proofers for a proof image output exist, and of the various types of proofers, a proofer for outputting a proof image is selected in accordance with, for example, speed and cost for producing the proof image, that is, for example, such a system that usually, a proof image is displayed on a display screen of a CRT display unit and is printed out by a printer as a need arises, and in addition for printing out there are prepared a plurality of printers, a printer for proof image output is selected in accordance with speed and cost for print output, or necessary image quality. In this case, according to the technology proposed in the above-mentioned Japanese Patent Application Laid Open Gazette Hei. 10-248017, there is a need to do over again producing both the first conversion system and the second conversion system for each type of the proofer. This is a problem in efficiency of data management. Alternatively, it is possible to prepare both the first conversion system and the second conversion system for each type of the proofer beforehand. However, each of the first conversion system and the second conversion system includes a greatly

large scale LUT which needs a large capacity of memory. A preparation of the conversion system requiring such a large capacity of memory in accordance with a type of the proofer needs a very large capacity of memory. This is a problem
5 from the view point of structure of the system and the cost.

SUMMARY OF THE INVENTION

In view of the foregoing, it is an object of the present invention to provide a color conversion method
10 adapted to a system which is high in accuracy of the color reproduction of the spot color, wherein a plurality of types of proofers each for outputting a proof image, a color conversion apparatus and a color conversion definition storage medium for storing therein a color
15 conversion definition suitable for such a color conversion.

To achieve the above-mentioned object, the present invention provides a color conversion method of converting printing image data, which comprises process color image data defined by a coordinate value of a predetermined first
20 color space, and spot color image data defined by a coordinate value of a characteristic direction, into image data defined by a coordinate value of a predetermined second color space, for a proofer for outputting a proof
25 image based on the printing image data in accordance with a predetermined printing condition is reproduced, said color conversion method comprising:

a printing condition conversion step associated with a printing condition, of converting the coordinate value of the first color space into coordinate values of a colorimetry color space which is device-nondependent;

5 a spot color reference step of converting a spot color name into the coordinate values of the colorimetry color space;

10 a proof condition conversion step associated with a proof condition, of converting the coordinate values of the colorimetry color space into coordinate values of the second color space; and

15 a composition step of synthesizing, on the colorimetry color space or the second color space, image data defined by coordinate values of the colorimetry color space or the second color space, wherein the process color image data is converted, with image data defined by coordinate values of the colorimetry color space or the second color space, wherein the spot color name is converted,

20 wherein the printing image data, which comprises the process color image data defined by the coordinate value of the first color space, and the spot color image data defined by the coordinate value of the characteristic direction, is converted into the image data defined by the coordinate value of the second color space, for the proofer.

25

According to the color conversion method of the present invention as mentioned above, in the printing

condition conversion step, the print profile is used, in the spot color reference step, a chromaticity value such as L*a*b* value of the spot color, which will be offered from a maker of the spot color ink, is referred to, and in the proof condition conversion step, the proofer profile is used. Further, in the composition step, the process color image data and the spot color image data are combined. In this case, what is needed to be added or altered in accordance with addition or alteration of the proofer is only the proofer profile used in the proof condition conversion step. Thus, as compared with the technology disclosed in the above-mentioned Japanese Patent Application Laid Open Gazette Hei. 10-248017 in which there is a need to add or alter both the first conversion system and the second conversion system, which are of large scale, in accordance with addition or alteration of the proofer, according to the color conversion method of the present invention, it is possible to reduce an amount of addition of data resulting from addition of the proofer, and thus it is advantageous on a data management or on a memory capacity. Further, according to the color conversion method of the present invention, the conversion process for the spot color is set up independently of the conversion process for the process color. This feature makes it possible to obtain a proof image with great accuracy of color reproduction which is the same level as the technology disclosed in the above-mentioned Japanese Patent

Application Laid Open Gazette Hei. 10-248017.

In the color conversion method of the present invention as mentioned above, it is acceptable that said composition step is a step of synthesizing different types of image data on the second color space, or alternatively
5 that said composition step is a step of synthesizing different types of image data on the colorimetry color space.

In the event that said composition step is a step
10 of synthesizing different types of image data on the second color space, it is possible to adopt a color conversion method wherein of the printing image data, the process color image data defined by the coordinate value of the first color space is converted into image data defined by
15 the coordinate values of the colorimetry color space in said printing condition conversion step, and the image data defined by the coordinate values of the colorimetry color space thus obtained through the conversion is further converted into image data defined by the coordinate value
20 of the second color space in said proof condition conversion step,

the spot color name is converted into the coordinate values of the colorimetry color space in said spot color reference step, and the coordinate values of the
25 colorimetry color space thus obtained through the conversion is converted into the coordinate value of the second color space in said proof condition conversion step,

and

in said composition step, the image data defined by the coordinate value of the second color space, for the proofer, is synthesized in accordance with the image data defined by the coordinate value of the second color space, after conversion by said proof condition conversion step, the coordinate value of the second color space corresponding to the spot color, after conversion by said proof condition conversion step, and the spot color image data of the printing image data.

In the event that said composition step is a step of synthesizing different types of image data on the colorimetry color space, it is possible to adopt a color conversion method wherein of the printing image data, the process color image data defined by the coordinate value of the first color space is converted into image data defined by the coordinate values of the colorimetry color space in said printing condition conversion step,

the spot color name is converted into the coordinate values of the colorimetry color space in said spot color reference step,

in said composition step, the image data defined by the coordinate values of the colorimetry color space, for the proofer, is synthesized in accordance with the image data defined by the coordinate values of the colorimetry color space, after the conversion by said printing condition conversion step, the coordinate values

of the colorimetry color space corresponding to the spot color, after the conversion by said spot color reference step, and the spot color image data of the printing image data, and

5 the image data defined by the coordinate values of the colorimetry color space, for the proofer, which is synthesized by said composition step, is converted by said proof condition conversion step into the image data defined by the coordinate value of the second color space, for the
10 proofer.

Further, in the color conversion method of the present invention as mentioned above, in the event that said composition step is a step of synthesizing different types of image data on the second color space, it is
15 preferable that prior to conversion of the printing image data into the image data for the proofer, there is produced a process color conversion step in which the coordinate value of the first color space is directly converted into the coordinate value of the second color space in
20 accordance with said printing condition conversion step and said proof condition conversion step,

in conversion of the process color image data of the printing image data, there is applied said process color conversion step instead of individual application of
25 both said printing condition conversion step and said proof condition conversion step, so that of the printing image data, the process color image data defined by the

coordinate value of the first color space is converted into image data defined by the coordinate value of the second color space before synthesized with the spot color image data.

5 In the event that prior to the actual color conversion, the above-mentioned process color conversion step is produced, it takes time at the preparation stage by the corresponding production of the process color conversion step. But in the actual color conversion, the
10 process color image data is converted from the first color space to the second color space directly without passing through the colorimetry color space, and thus it is possible to contribute to enhancement of efficiency of the color conversion.

15 To achieve the above-mentioned object, the present invention provides a color conversion apparatus for converting printing image data, which comprises process color image data defined by a coordinate value of a predetermined first color space, and spot color image data
20 defined by a coordinate value of a characteristic direction, into image data defined by a coordinate value of a predetermined second color space, for a proofer for outputting a proof image in which an image obtained through printing of an image based on the printing image data in
25 accordance with a predetermined printing condition is reproduced, said color conversion apparatus comprising:

a definition storage section for storing

5 a first coordinates conversion definition
associated with a printing condition, defining an
association between the coordinate value of the first color
space and the coordinate values of a colorimetry color
space which is device-nondependent,

a spot color and coordinates conversion definition
defining an association between a spot color name and the
coordinate values of the colorimetry color space,

10 a second coordinates conversion definition
defining an association between the coordinate values of
the colorimetry color space and the coordinate value of the
second color space, and

15 a coordinates composition definition defining an
association among coordinate values of the colorimetry
color space or the second color space, wherein the process
color image data is converted, on the colorimetry color
space or the second color space, coordinate values of the
colorimetry color space or the second color space, wherein
the spot color name is converted, and a set of coordinate
20 values wherein said two types of coordinate values are
synthesized; and

25 a color conversion section for converting the
printing image data, which comprises the process color
image data defined by the coordinate values of the first
color space and the spot color image data defined by the
coordinate values of the characteristic direction, into the
image data defined by the coordinate value of the second

color space, for the proofer, referring to said first coordinates conversion definition, said spot color and coordinates conversion definition, said second coordinates conversion definition, and said coordinates composition definition, which are stored in said definition storage section.

According to the color conversion apparatus of the present invention as mentioned above, it is possible to suppress a degree of an increment of a memory capacity of the definition storage section, and also possible to perform a color conversion with great accuracy for outputting a proof image.

In the color conversion apparatus of the present invention as mentioned above, it is acceptable that said coordinates composition definition, which is stored in said definition storage section, defines an association between said two types of coordinate values of the second color space and said set of coordinate values, and said color conversion section comprises:

first conversion means for converting the process color image data defined by the coordinate value of the first color space, of the printing image data, into image data defined by the coordinate values of the colorimetry color space, referring to said first coordinates conversion definition;

second conversion means for converting the spot color name into the coordinate values of the colorimetry

color space, referring to said spot color and coordinates conversion definition;

third conversion means for converting the image data defined by the coordinate values of the colorimetry color space, after conversion by said first conversion means, into image data defined by the coordinate value of the second color space, referring to said second coordinates conversion definition;

fourth conversion means for converting the coordinate values of the colorimetry color space, associated with the spot color, after conversion by said second conversion means, into the coordinate value of the second color space, referring to said second coordinates conversion definition;

first composition means for synthesizing the image data defined by the coordinate value of the second color space, for the proofer, in accordance with the image data defined by the coordinate value of the second color space, after conversion by said third conversion means, the coordinate value of the second color space corresponding to the spot color, after conversion by said fourth conversion means, and the spot color image data of the printing image data, referring to said coordinates composition definition.

In the color conversion apparatus of the present invention as mentioned above, alternatively, it is acceptable that said coordinates composition definition, which is stored in said definition storage section, defines

an association between said two types of coordinate values of the colorimetry color space and said set of coordinate values, and said color conversion section comprises:

5 fifth conversion means for converting the process color image data defined by the coordinate value of the first color space, of the printing image data, into image data defined by the coordinate values of the colorimetry color space, referring to said first coordinates conversion definition;

10 sixth conversion means for converting the spot color name into the coordinate values of the colorimetry color space, referring to said spot color and coordinates conversion definition;

15 second composition means for synthesizing the image data defined by the coordinate values of the colorimetry color space, for the proofer, in accordance with the image data defined by the coordinate values of the colorimetry color space, after conversion by said fifth conversion means, the coordinate values of the colorimetry
20 color space corresponding to the spot color, after conversion by said sixth conversion, and the spot color image data of the printing image data, referring to said coordinates composition definition; and

25 seventh conversion means for converting the image data defined by the coordinate values of the colorimetry color space, for the proofer, which is synthesized by said second composition means, into the image data defined by

the coordinate value of the second color space, for the proofer, referring to said second coordinates conversion definition.

In the color conversion apparatus of the present invention as mentioned above, further alternatively it is acceptable that said coordinates composition definition, which is stored in said definition storage section, defines an association between said two types of coordinate values of the colorimetry color space and said set of coordinate values, and said color conversion section comprises:

coordinates conversion definition construction means for constructing a third coordinates conversion definition to directly associate the coordinate value of the first color space with the coordinate value of the second color space in accordance with said first coordinates conversion definition and said second coordinates conversion definition;

eighth conversion means for converting the process color image data defined by the coordinate value of the first color space, of the printing image data, into image data defined by the coordinate values of the second color space, referring to said third coordinates conversion definition;

ninth conversion means for converting the spot color name into the coordinate values of the colorimetry color space, referring to said spot color and coordinates conversion definition;

tenth conversion means for converting the coordinate values of the colorimetry color space corresponding to the spot color, after conversion by said ninth conversion means, into the coordinate value of the second color space, referring to said second coordinates conversion definition; and

third composition means for synthesizing the image data defined by the coordinate values of the second color space, for the proofer, in accordance with the image data defined by the coordinate values of the second color space, after conversion by said eighth conversion means, the coordinate values of the second color space corresponding to the spot color, after conversion by said ninth conversion, and the spot color image data of the printing image data, referring to said coordinates composition definition.

To achieve the above-mentioned object, the present invention provides a color conversion definition storage medium storing a color conversion definition for converting printing image data, which comprises process color image data defined by a coordinate value of a predetermined first color space, and spot color image data defined by a coordinate value of a characteristic direction, into image data defined by a coordinate value of a predetermined second color space, for a proofer for outputting a proof image in which an image obtained through printing of an image based on the printing image data in accordance with a

predetermined printing condition is reproduced, said color conversion definition comprising:

5 a first coordinates conversion definition associated with a printing condition, defining an association between the coordinate value of the first color space and the coordinate values of a colorimetry color space which is device-nondependent;

10 a spot color and coordinates conversion definition defining an association between a spot color name and the coordinate values of the colorimetry color space;

15 a second coordinates conversion definition defining an association between the coordinate values of the colorimetry color space and the coordinate value of the second color space, said second coordinates conversion definition being associated with a proof condition; and

20 a coordinates composition definition defining an association among coordinate values of the colorimetry color space or the second color space, wherein the process color image data is converted, on the colorimetry color space or the second color space, coordinate values of the colorimetry color space or the second color space, wherein the spot color name is converted, and a set of coordinate values wherein said two types of coordinate values are synthesized.

25 The color conversion definition stored in the color conversion definition storage medium of the present invention is suitable for an increment of a proofer and the

like, and adoption of such a color conversion definition to perform a color conversion makes it possible to perform a color conversion with great accuracy in color reproduction of a spot color.

5 Incidentally, it is acceptable that the various types of "definition" as mentioned above is data of a table structure, for example, LUT, or another structure; a program for executing an arithmetic operation based on a conversion formula; or alternatively a combination of data and a program, such as a combination of data of LUT
10 structure and a program for executing interpolation arithmetic operations.

BRIEF DESCRIPTION OF THE DRAWINGS

15 Fig. 1 is a construction view of a system for producing print and proof image, to which an embodiment of the present invention is applied.

 Fig. 2 is a perspective view of the personal computer shown in Fig. 1.

20 Fig. 3 is a hardware construction view of the personal computer.

 Fig. 4 is a conceptual view of a print profile constituting part of the color conversion definition.

25 Fig. 5 is a conceptual view of a print profile constituting part of the color conversion definition.

 Fig. 6 is a conceptual view of the color conversion definition for directly converting coordinate

values of CMYK color spaces to coordinate values of RGB color spaces, which is produced through a combination of a print profile and a printer profile.

Fig. 7 is a typical illustration of spot color and coordinates conversion definition constituting part of the color conversion definition.

Fig. 8 is a typical illustration of coordinates composition definition constituting part of the color conversion definition.

Fig. 9 is a view showing a first embodiment of a color conversion method according to the present invention.

Fig. 10 is a view showing a second embodiment of a color conversion method according to the present invention.

Fig. 11 is a view showing a modification of the second embodiment of a color conversion method according to the present invention.

Fig. 12 is a view showing a third embodiment of a color conversion method according to the present invention.

Fig. 13 is a functional block diagram of the first embodiment of a color conversion apparatus according to the present invention.

Fig. 14 is a functional block diagram of a color conversion section of the second embodiment of a color conversion apparatus according to the present invention.

Fig. 15 is a functional block diagram of a color conversion section of the third embodiment of a color conversion apparatus according to the present invention.

DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS

Embodiments of the present invention will be described with reference to the accompanying drawings.

Fig. 1 is a construction view of a system for
5 producing print and proof image, to which an embodiment of the present invention is applied.

A color scanner 10 reads an original image and generates color separation image data for four colors of CMYK representative of the original image. The image
10 data for four colors of CMYK is fed to a workstation 20. In the workstation 20, an electronic page make-up is performed in accordance with entered image data by an operator and image data representative of an image for printing is generated. Here, an operator, who operates the
15 workstation 20, determines that printing using some spot color ink as well as process color ink of four colors of CMYK is performed, and in the electronic page make-up an image including the spot color is designed. Accordingly, here, as printing image data representative of the image
20 for printing, there are generated process color image data defined in form of coordinate values (combination of dot % of C, M, Y, K) for the color space (an example of the first color space referred to in the present invention) of four colors of CMYK and spot color image data defined in
25 form of coordinate values (dot % of the spot color) of the characteristic direction, for spot color to be adopted. The printing image data, which comprises the process color

image data and the spot color image data, is fed to a film printer 30 in the event that a printing is to be performed. The film printer 30 produces a printing film original plate, which comprises each plate for CMYK and a plate for spot color, in accordance with the entered printing image data.

A printing plate is produced from the printing film original plate, and the produced printing plate is loaded onto a printing machine 40. Ink is applied to the printing plate loaded onto the printing machine. The applied ink is transferred to a printing paper to form an image 41 on the printing paper. The ink used at that time is process color ink for four colors of CMYK and a predetermined spot color ink. On the image 41, there exists an image portion 41a printed with the spot color ink. Incidentally, the spot color ink to be used for once printing is not restricted to one sort of spot color ink. However, for the convenience of explanation, there will be explained the embodiment assuming that the spot color ink to be used is only one sort of spot color ink.

Such a series of work that the film printer 30 is used to produce a film original plate, a printing plate is produced and loaded onto the printing machine 40, and ink is applied to the printing plate to perform a printing on a paper is large-scale work and costs a lot. For this reason, prior to perform an actual printing work, a proof image 61 is produced by a proofer in a manner as set forth below so that a finish of the printed image 41 is confirmed

beforehand.

To produce a proof image, printing image data, which is produced by an electronic page make-up on the workstation 20, is fed to a personal computer 50. Here, the image data fed to the personal computer 50 is a description language data described with a so-called PDL (Page Description Language). The personal computer 50 converts the description language data into process image data for four colors of CMYK and spot color image data associated with a spot color, which are developed into a bit map by a so-called RIP (Raster Image Processor). Combined image data of the process image data for four colors of CMYK and the spot color image data for a spot color is substantially the same as the printing image data to be fed to the film printer 30.

The process color image data for and the spot color image data are converted into image data for three colors of RGB suitable for a proofer (here a printer 60a), which intends to output a proof image, of a plurality of proofers comprising a plurality of printers 60a, 60b, ... , and a CRT display 60n, through referring to a color conversion definition inside the personal computer 50. The printer 60a receives the image data for three colors of RGB and produces the proof image 61 in accordance with the entered image data for three colors of RGB.

A degree of coincidence of colors of the image 41 obtained through printing by the printing machine 40 and

the proof image obtained by the printer 60a is determined by a color conversion definition in the personal computer 50. The color conversion definition is produced for each proofer (for each proof condition).

5 While Fig. 1 shows only one printing machine, it is acceptable that a plurality of printing machines exist. Or alternatively, it is acceptable that while only one printing machine is provided, a plurality of printing conditions, which are mutually different, exist. The color
10 conversion definition is produced in accordance with each of the plurality of printing conditions including the difference of the printing machines. More in details, the color conversion definition is produced in accordance with a combination of each printing condition and each proofer
15 (each proof condition in the event that only one proofer is provided and a plurality of proof condition exist). The color conversion definition will be described later. Also a colorimeter will be described later.

20 In this manner, a proof image is produced and the proof image is confirmed. Thus, it is possible to confirm a finish of printing beforehand.

25 An aspect of the embodiment of the present invention in the proof image producing system resides in processing contents to be executed inside the personal computer 50. Hereinafter, there will be described the personal computer 50.

Fig. 2 is a perspective view of the personal

computer 50 shown in Fig. 1. Fig. 3 is a hardware construction view of the personal computer 50.

The personal computer 50 comprises a main frame 51, an image display unit 52 for displaying an image on a display screen 52a in accordance with an instruction from the main frame 51, a keyboard 53 for entering information according to a key operation to the main frame 51, and a mouse 54 for entering an instruction according to, for example, an icon displayed on an arbitrarily position on the display screen 52a through designation. The main frame 51 is provided with a floppy disk loading slot 51a for loading a floppy disk, and a CD-ROM loading slot 51b for loading a CD-ROM.

The main frame 51 incorporates therein, as shown in Fig. 3, a CPU 511 for executing various sorts of program, a main memory 512 wherein a program stored in a hard disk unit 513 is read out and developed for the purpose of execution by the CPU 511, the hard disk unit 513 storing various sorts of programs and data, an FD driver 514 for accessing a floppy disk 100 loaded onto the FD driver 514, a CD-ROM driver 515 for accessing a CD-ROM 110 loaded onto the CD-ROM driver 515, an input interface 516 connected with the workstation 20 (cf. Fig. 1) for receiving image data from the workstation 20, and an output interface 517 for transmitting image data to the printers 60a, 60b, ... , and the CRT display 60n which are used as the proofers. Those elements are mutually connected with the image

display unit 52, the keyboard 53 and the mouse 54 via a bus 55. It is acceptable that the image display unit 52 shown in Figs. 2 and 3 is used as one of the proofers.

The CD-ROM 110 stores therein a color conversion program for causing the personal computer 50 to operate as a color conversion apparatus. Such CD-ROM 110 is loaded on the CD-ROM driver 515, so that the color conversion program stored in the CD-ROM 110 is up-loaded onto the personal computer 50 and is stored in the hard disk unit 513.

Next, there will be described a method of producing a color conversion definition constructed in the personal computer 50.

Fig. 4 is a conceptual view of a print profile constituting part of the color conversion definition.

As mentioned above, in many cases, a print profile associated with a typical printing condition is provided from a printer (a printing service trader), and thus as far as a print profile associated with a desired print condition is available, there is no need to produce a print profile. Here, however, there will be explained a basic method of producing a print profile in the event that the print profile is newly produced.

Dot % data for four colors of CMYK to be generated from the workstation shown in Fig. 1 is sequentially altered, for example, such as 0%, 10%, ..., 100% , so that color patch images based on the dot % data thus generated are produced in accordance with the above-

mentioned printing procedure. A colorimeter 200 is used to measure color patches constituting a color patch image wherein while the image 41 shown in Fig. 1 is not an image representative of a color patch image, it is assumed that a color patch image is printed instead of the image 41. This makes it possible to constitute a print profile representative of the association between coordinate values on a color space (a first color space referred to in the present invention) for four colors of CMYK and coordinate values on a colorimetry color space (here $L^*a^*b^*$ color space). This print profile corresponds to an example of a first coordinates conversion definition referred to in the present invention.

Here, in production of the color patch for producing the print profile, only process color ink for four colors of CMYK is used and spot color ink is not used. The reason why this is to do so is that addition of the spot color ink causes the produced print profile to be lost in generality or universality, and it is very troublesome that various sorts of spot color ink are prepared and a print profile is established for each combination of spot color ink.

Fig. 5 is a conceptual view of a print profile constituting part of the color conversion definition.

As mentioned above, also with respect to the printer profile, in many cases, it is provided from a printer maker. Thus, as far as a printer profile

associated with a desired printer (here the printer 60a shown in Fig. 1) is available, there is no need to produce the printer profile. Nevertheless, there will be explained a basic method of producing a printer profile in the event that the printer profile is newly produced. The method of producing a printer profile is similar to the above-mentioned method of producing a print profile.

Here, the personal computer 50 shown in Fig. 1 is used to sequentially vary image data for three colors of RGB on each color in a predetermined numbers of step (e.g. 8 steps) from the minimum value (e.g. 0) to the maximum value (e.g. 255), so that a color patch image is produced in accordance with the image data thus sequentially generated. A colorimeter 200 is used to measure color patches constituting a color patch image wherein while the image 61 shown in Fig. 1 is not an image representative of a color patch image, it is assumed that a color patch image is outputted instead of the image 61. This makes it possible to constitute a printer profile representative of the association between coordinate values on a color space (a second color space referred to in the present invention) for three colors of RGB and coordinate values on a colorimetry color space (here $L^*a^*b^*$ color space), on the printer 60a.

This printer profile is used for converting coordinate values on the $L^*a^*b^*$ color space to coordinate values on the color space for three colors of RGB, and

corresponds to an example of a second coordinates conversion definition referred to in the present invention.

Fig. 6 is a conceptual view of the color conversion definition for directly converting coordinate values of a CMYK color space to coordinate values of an RGB color space, which is produced through a combination of a print profile and a printer profile.

Here, there is constructed a third color conversion definition in which the print profile (a first color conversion definition) is combined with the printer profile (a second color conversion definition), so that coordinate values of a CMYK color space are converted into coordinate values of an RGB color space directly without passing through an $L^*a^*b^*$ color space.

The third color conversion definition is used in some embodiment of a various types of embodiments of the present invention which are described later.

Fig. 7 is a typical illustration of spot color and coordinates conversion definition constituting part of the color conversion definition.

The spot color and coordinates conversion definition is to associate a spot color name and coordinate values on $L^*a^*b^*$ color space of the spot color ink. With respect to the coordinate values on $L^*a^*b^*$ color space of the spot color ink, generally, information is available from a maker of the spot color ink. Nevertheless, in the event that it is intended to determine the coordinate

values on $L^*a^*b^*$ color space of the spot color ink, data, wherein dot % of monochrome of the spot color ink is 100%, is generated, a patch of the solid of the spot color is produced based on the data in accordance with the above-mentioned printing procedure, and the patch of the solid is measured by the colorimeter thereby determining the coordinate values on $L^*a^*b^*$ color space.

That is, the spot color and coordinates conversion definition shown in Fig. 6 determines coordinate values of on $L^*a^*b^*$ color space of the solid patch wherein dot % of the spot color represented by the spot color name is 100%.

Fig. 8 is a typical illustration of coordinates composition definition constituting part of the color conversion definition.

By way of the coordinates composition definition, there is raised a coordinates composition definition in which coordinate values on RGB color space (an example of the second color space referred to in the present invention) are synthesized.

The coordinates composition definition receives image data defined by coordinate value of RGB color space, resulted from process color image data for four colors of CMYK of printing image data, coordinate values on RGB color space for spot color, resulted from coordinate values of $L^*a^*b^*$ color space of the solid of the spot color obtained through referring to the spot color and coordinates conversion definition shown in Fig. 7, and

dot % data (spot color image data) of the spot color,
which constitutes the printing image data. In the
coordinates composition definition, by way of example, the
respective data for R, G, B defined by coordinate values
5 on RGB color space, which are determined by coordinate
values (associated with dot % :100%) on RGB color space,
as to the spot color, and dot % represented by spot color
image data, and the respective data for R, G, B resulted
from the process color image data of the printing image
10 data, are added to one another. The coordinates
composition definition generates image data for R, G, B
so as to output a proof image from a proofer (here the
printer 60a shown in Fig. 1) for a proof image output
through, for example, the above-mentioned arithmetic
15 operation or an LUT corresponding to such an arithmetic
operation.

While there is explained the coordinates
composition definition wherein coordinates are synthesized
on RGB color space, the coordinates composition
20 definition is not restricted to one wherein coordinates are
synthesized on RGB color space. It is acceptable that
the coordinates composition definition is one wherein
coordinates are synthesized on $L^*a^*b^*$ color space. This
is simply different in color space representative of
25 coordinates. Thus, there will be omitted in figure and
explanation for the coordinates composition definition
taking $L^*a^*b^*$ color space other than RGB color space.

Fig. 9 is a view showing a first embodiment of a color conversion method according to the present invention.

Fig. 9 shows a print condition conversion process 311, a spot color reference process 312, a printer condition conversion process 313 (an example of the proof condition conversion process referred to in the present invention) and a composition process 314.

In the print condition conversion process 311, the print profile (the first color conversion definition), which is explained in conjunction with Fig. 4, is referred to so that process color image data defined by coordinate values on CMYK color space of the printing image data is converted into image data defined by coordinate values on L*a*b* color space.

In the spot color reference process 312, the spot color and coordinates conversion definition explained in conjunction with Fig. 7 is referred to so that the spot color name is converted into coordinate values on L*a*b* color space as to the spot color.

In the printer condition conversion process 313, the printer profile (the second color conversion definition), which is explained in conjunction with Fig. 5, is referred to so that image data defined by coordinate values on L*a*b* color space, which is obtained in the print condition conversion process 311, is converted into image data defined by coordinate values on RGB color space, and further coordinate values on L*a*b* color space,

which is obtained in the spot color reference process 312,
is converted into coordinate values on RGB color space.

Further, in the composition process 314, the image
data defined by coordinate values on RGB color space,
5 which is obtained in the printer condition conversion
process 313, the coordinate values on RGB color space
with respect to the spot color, which is also obtained in
the printer condition conversion process 313, and the
dot % data of the spot color are synthesized into image
10 data for proof image output, which is defined by the
coordinate values on RGB color space, in accordance with
the coordinates composition definition explained referring
to Fig. 8.

The image data on RGB color space obtained in the
15 composition process 314 is transmitted to the printer 60a
for proof image output, shown in Fig. 1, so as to print-out
a proof image in accordance with the transmitted image data.

According to the color conversion method shown in
Fig. 9, it is possible to obtain a proof image excellent in
20 color reproduction with respect to spot color too, since
the process color for CMYK and the spot color are
subjected to data conversion through the respective
different path and then synthesized. Further, according to
the color conversion method shown in Fig. 9, what is needed
25 to be altered when a printer for outputting a proof image
is altered is only a printer profile referred to in the
printer condition conversion process. This makes it

possible to reduce a load of the data management as compared with the method disclosed in the above-mentioned Japanese Patent Application Laid Open Gazette Hei. 10-248017.

5 Fig. 10 is a view showing a second embodiment of a color conversion method according to the present invention.

 According to the second embodiment of a color conversion method shown in Fig. 10, there is provided a composition process 315 for performing composition of data on L*a*b* color space. In the composition process 315, the image data defined by coordinate values on L*a*b* color space, which is obtained in the print condition conversion process 311, the coordinate values on L*a*b* color space with respect to the spot color, which is
10 obtained in the spot color reference process 312, and the dot % data of the spot color are synthesized into image data for printer, which is defined by the coordinate values on L*a*b* color space, in accordance with the coordinates composition definition explained referring to Fig. 8 (for
15 performing an arithmetic operation on L*a*b*. The image data defined by the coordinate values on L*a*b* color space, which is obtained in the composition process, is converted into image data for a printer, which is defined by coordinate values on RGB color space, referring to the
20 printer profile (the second color conversion definition) shown in Fig. 5 in the printer condition conversion process 313. The image data on RGB color space, which is
25

obtained through conversion in the printer condition conversion process 313, is transmitted to the printer 60a for proof image output shown in Fig. 1, in a similar fashion to that of the first embodiment of the present invention shown in Fig. 9. In the printer 60a, a proof image is printed out in accordance with the transmitted image data.

Also in the color conversion method shown in Fig. 10, in a similar fashion to that shown in Fig. 9, the process color for CMYK and spot color are individually converted into coordinate values on $L^*a^*b^*$ color spaces and then synthesized. Thus, it is possible to obtain a proof image excellent in color reproduction with respect to spot color too. Further, according to the color conversion method shown in Fig. 10, what is needed to be altered when a printer for outputting a proof image is altered is only a printer profile referred to in the printer condition conversion process 313. This makes it possible to reduce a load of the data management.

Fig. 11 is a view showing a modification of the second embodiment of a color conversion method according to the present invention.

In the composition process 315, synthesis of coordinate values on $L^*a^*b^*$ color space is performed. More in details, in an $L^*a^*b^* \cdot XYZ$ conversion process 315a, coordinate values on $L^*a^*b^*$ color space are converted into coordinate values on XYZ color space. In

a composition process 315b, synthesis on XYZ color space is performed. In an XYZ \cdot L*a*b' conversion process 315c, coordinate values on XYZ color space after the synthesis are converted into coordinate values on L*a*b' color space.

5 The XYZ color space is associated with luminosity more directly than the L*a*b' color space, and thus it is possible to perform synthesis which involves few errors.

10 Fig. 12 is a view showing a third embodiment of a color conversion method according to the present invention. There will be described different points from the first embodiment shown in Fig. 9.

15 In a process conversion process producing process 316, prior to conversion of image data for printing into image data for printer, the print profile (the first color conversion definition) explained referring to Fig. 4 and the printer profile (the second color conversion definition) explained referring to Fig. 5 are synthesized into a single color conversion definition (the third color conversion definition), as shown in Fig. 6.

20 After those preparation, the printing image data is converted into the image data for printer. In this case, with respect to the process color image data for four colors of CMYK of the printing image data, in process
25 color conversion process 317 instead of both the processes of the print condition conversion process 311 and the printer condition conversion process 313, which are shown

in Fig. 9, the process color image data for four colors of CMYK is directly converted into the image data for three colors of RGB.

5

With respect to the conversion process and the composition process related to the spot color, they are the same as those of the first embodiment shown in Fig. 9, and thus the redundant explanation will be omitted.

10

In case of the color conversion method shown in Fig. 12, as compared with the color conversion method according to the first embodiment shown in Fig. 9, there is a need to produce the third color conversion definition shown in Fig. 6 at the preparation step. However, according to the color conversion method shown in Fig. 12, in the actual color conversion, it is possible to reduce the process of the coordinates conversion by one and thereby contributing to a higher speed for color conversion.

15

20

Fig. 13 is a functional block diagram of the first embodiment of a color conversion apparatus according to the present invention.

25

The color conversion apparatus is implemented by combination of the personal computer 50 shown in Figs. 2 and 3 and a program which is executed by the personal computer 50.

The color conversion apparatus shown in Fig. 13 comprises a designation section 601, a definition storage

section 602 and a color conversion section 603.

The definition storage section 602 stores therein a plurality of first coordinates conversion definitions (print profiles) (cf. Fig. 4 and the associated

5 description) 6021a, 6021b, ..., 6021p associated with print conditions, a plurality of spot color and coordinates conversion definitions 6022a, 6022b, ..., 6022q (cf. Fig. 7 and the associated description) associated with various spot colors, coordinate composition definition 6023 (cf.

10 Fig. 8 and the associated description), and a plurality of second coordinates conversion definitions (printer profiles) (cf. Fig. 5 and the associated description) 6024a, 6024b, ..., 6024r associated with proof conditions. With respect to the second coordinates conversion definitions, 15 in Fig. 5, they are referred to as the printer profile since it has been explained on the assumption that the proof image is printed out by the printer 60a shown in Fig. 1. However it is noted that the second coordinates conversion definitions includes the coordinates conversion 20 definition associated with CRT display 60n shown in Fig. 1.

The definition storage section 602 is disposed inside the hard disk unit 513 shown in Fig. 3. And the definition storage section 602 (the hard disk unit 513 shown in Fig. 3) also corresponds to one embodiment of a 25 color conversion definition storage medium of the present invention.

The designation section 601 performs designation

of print conditions, designation of proof conditions
(designation of a proofer which outputs a proof image), and
designation of spot color used in printing. The keyboard
53 or the mouse 54 shown in Figs. 2 and 3 may serve as the
5 designation section 601. Incidentally, it is acceptable
that designations of the print conditions and spot colors
are not performed through the designation section 601, but
the associated information is derived from the workstation
20 shown in Fig. 1.

10 When print condition is designated through the
designation section 601, of the plurality of first
coordinates conversion definitions 6021a, 6021b, ..., 6021p
which are stored in the definition storage section 602, a
first coordinates conversion definition (here the first
15 coordinates conversion definition 6021a) associated with
the designated print condition is read out and fed to the
color conversion section 603. Similarly, when spot color
is designated through the designation section 601, of the
plurality of spot color and coordinates conversion
20 definitions 6022a, 6022b, ..., 6022q which are stored in the
definition storage section 602, a spot color and
coordinates conversion definition (here the spot color and
coordinates conversion definition 6022a) associated with
the designated spot color is read out and fed to the color
25 conversion section 603. Further, when a printer for
outputting a proof image or a CRT display unit is
designated through the designation section 601, of the

plurality of second coordinates conversion definitions 6024a, 6024b, ..., 6024r which are stored in the definition storage section 602, a second coordinates conversion definition (here the second coordinates conversion definition 6024a) associated with the designated proofer (here the printer 60a) is read out and fed to the color conversion section 603.

Further, the coordinate composition definition 6023 is also read out from the definition storage section 602 and is fed to the color conversion section 603.

In this manner, a single color conversion definition, which comprises the first coordinates conversion definition 6021a, the spot color and coordinates conversion definition 6022a, the coordinate composition definition 6023, and the second coordinates conversion definition 6024a, is fed to the color conversion section 603, and thereafter, image data of PLD type for print image, which is produced by the electronic page make-up, is fed from the workstation 20 shown in Fig. 1 to the personal computer 50 (cf. Figs. 1 to 3) with which the color conversion apparatus shown in Fig. 13 is implemented, so that the image data of PDL type is converted by RIP into a bit map type of image data, and process color image data defined by CMYK color space for print, of the bit map, and spot color image data representative of dot % of spot color of the bit map are fed to the color conversion section 603. Further fed to the color conversion section

603 is data representative of a spot color name designating a spot color.

In the color conversion section 603, color conversion based on the color conversion definition, which is inputted to the color conversion section 603 beforehand, is performed in accordance with the entered process color image data for four colors of CMYK, spot color image data and spot color name, so that image data for RGB is generated to derive a proof image using the printer 60a (cf. Fig. 1). The image data for RGB generated through the color conversion in the color conversion section 603 is transmitted to the printer 60a so as to output a proof image of color coincident to color of the printing matter including a printed portion by the spot color.

Hereinafter, there will explained color conversion means in the color conversion section 603.

The color conversion section 603 comprises first conversion means 6031, second conversion means 6032, third conversion means 6033, fourth conversion means 6034 and first composition means 6035.

Of the printing image data, the process color image data for four colors of CMYK is fed to the first conversion means 6031. In the first conversion means 6031, the first coordinates conversion definition (print profile) 6021a, which is read from the definition storage section 602 and fed to the color conversion section 603, is referred to so that the entered process color image data

for four colors of CMYK is converted into image data defined by coordinate values of L*a*b* color space.

The image data defined by coordinate values of L*a*b* color space, which is obtained through the conversion by the first conversion means 6031, is fed to the third conversion means 6033. In the third conversion means 6033, the second coordinates conversion definition (printer profile) 6024a, which is read from the definition storage section 602 and fed to the color conversion section 603, is referred to so that image data on L*a*b* color space entered to the third conversion means 6033 is converted into image data defined by coordinate values of RGB color space. The image data defined by coordinate values of RGB color space, which is obtained through the conversion by the third conversion means 6033, is fed to the first composition means 6035.

On the other hand, a spot color name is fed to the second conversion means 6032. In the second conversion means 6032, the spot color and coordinates conversion definitions 6022a, which is read from the definition storage section 602 and fed to the color conversion section 603, is referred to so that the spot color name fed to the second conversion means 6032 is converted into coordinate values of L*a*b* color space. The coordinate values of L*a*b* color space, which is representative of the spot color, is fed to the fourth conversion means 6034. In the fourth conversion means 6034, in a similar fashion to that

of the third conversion means 6033, the second coordinates conversion definition (printer profile) 6024a is referred to so that image data on L*a*b* color space representative of the spot color is converted into coordinate values of RGB color space. The coordinate values of RGB color space representative of the spot color, which is obtained through the conversion by the fourth conversion means 6034, is fed to the first composition means 6035.

Fed to the first composition means 6035 are the spot color image data (dot % data) as well as the image data of RGB obtained through the conversion by the third conversion means 6033 and the RGB coordinate values of the spot color. In the first composition means 6035, the coordinate composition definition 6023, which is read from the definition storage section 602 and fed to the color conversion section 603, is referred to so that RGB coordinate values of dot % data of the spot color, which is determined by the RGB coordinate values of the solid of the spot color entered from the fourth conversion means 6034 and dot % of the spot color represented by the spot color image data, and RGB coordinate values of image data entered from the third conversion means 6033 are synthesized to generate image data defined by coordinate values of RGB color space, for a proof image output.

In this manner, the image data of RGB obtained through the color conversion by the color conversion

section 603 is transmitted to the printer 60a (cf. Fig. 1), as mentioned above, to output a proof image based on the image data of RGB.

As mentioned also in the embodiments of the color conversion method of the present invention, the process color and the spot color are subjected to a color conversion through individual conversion systems and then synthesized. Thus, it is possible to perform a color conversion suitable for the process color and the spot color and thereby obtain a proof image excellent in color reproduction with respect to spot color as well as the process color. Further, according to the color conversion method shown in Fig. 13, what is needed to be added or altered when a proofer for outputting a proof image is added or altered is only the second coordinates conversion definition. This makes it possible to reduce a load of the data management. Further, it is possible to reduce an increment of memory capacity of the definition storage section 602, resulting from addition of the proofer.

Fig. 14 is a functional block diagram of a color conversion section of the second embodiment of a color conversion apparatus according to the present invention. The structure of the designation section and the definition storage section is the same as those in the first embodiment shown in Fig. 13, and thus redundant description will be omitted. It is noted that in the second embodiment shown in Fig. 14, the coordinate composition definition

6023 stored in the definition storage section 602 shown in Fig. 13 is one defining coordinates composition on L*a*b*.

A color conversion section 613 shown in Fig. 14 comprises a fifth conversion means 6131, a sixth conversion means 6132, a second composition means 6133 and a seventh conversion means 6134.

The fifth conversion means 6131 and the sixth conversion means 6132 are the same as the first conversion means 6031 and the second conversion means 6032 of the color conversion section 603 of the first embodiment shown in Fig. 13 in their function, respectively. And thus the redundant description will be omitted.

Fed to the second composition means 6133 are the image data of L*a*b* obtained through the conversion by the fifth conversion means 6131, coordinate values on L*a*b* color space of the spot color, which is obtained through the conversion by the sixth conversion means 6132, and spot color image data (dot % data). In the second composition means 6133, the coordinate composition definition, which performs coordinates composition on the L*a*b* color space, is referred to so that L*a*b* coordinate values of the spot color image data, which is determined by L*a*b* coordinate values of the solid of the spot color entered from the sixth conversion means 6132 and dot % of the spot color represented by the spot color image data, and L*a*b* coordinate values of process image data entered from the fifth conversion means 6131 are

synthesized to generate image data (on L*a*b* color space) for a proof image output. The image data defined by the coordinate values of L*a*b* color space for a proof image output is fed to the seventh conversion means 6134.

- 5 In the seventh conversion means 6134, the second coordinates conversion definitions 6024a is referred to so that image data of L*a*b* for a proof image output is converted into image data of RGB for a proof image output.

- 10 The image data of RGB for a proof image output is transmitted to the printer 60a shown in Fig. 1. In the printer 60a, a proof image based on the image data of RGB thus transmitted is outputted.

- 15 While it is acceptable that the second composition means 6133 in the second embodiment shown in Fig. 14 is one for directly performing a coordinates synthesis in L*a*b* color space, in a similar fashion to that of the embodiment of the color conversion method explained referring to Fig. 11, it is acceptable that the second composition means 6133 is one in which coordinate values of L*a*b* color space is
20 once converted into coordinate values of XYZ color space, coordinates synthesis is performed on XYZ color space, and then again coordinate values of XYZ color space is converted into coordinate values of L*a*b* color space.

- 25 Also in the second embodiment shown in Fig. 14, the process color and the spot color are individually subjected to the color conversion and then synthesized. Thus, also with respect to the spot color, it is possible

to expect an excellent color reproduction. It is similar to that of the first embodiment also in the point that an increment of the memory capacity resulted from the printer for a proof image output may be reduced.

5 Fig. 15 is a functional block diagram of a color conversion section of the third embodiment of a color conversion apparatus according to the present invention. The structure of the designation section and the definition storage section in the third embodiment is the same as
10 those in the first embodiment shown in Fig. 13, and thus redundant description will be omitted.

A color conversion section 623 shown in Fig. 15 comprises a coordinates conversion definition construction means 6231, an eighth conversion means 6232, a ninth
15 conversion means 6233, a tenth conversion means 6234 and a third composition means 6235. The ninth conversion means 6233, tenth conversion means 6234 and the third composition means 6235 are the same as the second conversion means 6032, the fourth conversion means 6034, and the first composition
20 means 6035 of the color conversion section 603 of the first embodiment shown in Fig. 13 in their function, respectively. And thus the redundant description will be omitted.

In the coordinates conversion definition construction means 6231, as explained referring to Fig. 6,
25 the first coordinates conversion definition (print profile) 6021a, which is read out from the definition storage section 602 and fed to the color conversion section 623, is

combined with the second coordinates conversion definition (printer profile) 6024a, so that there is constructed the third coordinates conversion definition for converting coordinate values of CMYK color space into coordinate values of RGB color space directly without passing through L*a*b* color space.

Process color image data for CMYK is fed to the eighth conversion means 6232. In the eighth conversion means 6232, the third coordinates conversion definition constructed by the coordinates conversion definition construction means 6231 is referred to so that the entered process image data for CMYK is converted directly into image data for RGB.

In this manner, according to the third embodiment shown in Fig. 15, while there is a need to provide the coordinates conversion definition construction means 6231, and in addition, before the color conversion, to perform an arithmetic operation for constructing the third coordinates conversion definition, it is possible in the actual color conversion to convert the process color image data of CMYK to image data of RGB directly and thereby performing high speed color conversion.

With respect to a point that a color reproduction ability of spot color in the proof image is excellent and a point that an increment of a memory capacity, wherein a proofer is added, may be reduced, it is the same as that of the first embodiment shown in Fig. 13.

Incidentally, according to the above-mentioned
embodiments, there are shown an example in which a printer
having a color space of RGB is used as a proofer. But,
according to the present invention, it is acceptable that a
5 printer having a color space of CMYK and a display
having a color space of RGB are adopted as a proofer.

As mentioned above, according to the present
invention, it is adapted to a system in which there exist a
plurality of types of proofers for outputting a proof image,
10 and it is possible to maintain an accuracy of color
reproduction of spot color at high degree.

While the present invention has been described with
reference to the particular illustrative embodiments, it is
not to be restricted by those embodiments but only by the
15 appended claims. It is to be appreciated that those skilled
in the art can change or modify the embodiments without
departing from the scope and spirit of the present invention.

WHAT IS CLAIMED IS:

1. A color conversion method of converting
printing image data, which comprises process color image
5 data defined by a coordinate value of a predetermined first
color space, and spot color image data defined by a
coordinate value of a characteristic direction, into image
data defined by a coordinate value of a predetermined
second color space, for a proofer for outputting a proof
10 image in which an image obtained through printing of an
image based on the printing image data in accordance with a
predetermined printing condition is reproduced, said color
conversion method comprising:

a printing condition conversion step associated
15 with a printing condition, of converting the coordinate
value of the first color space into coordinate values of a
colorimetry color space which is device-nondependent;

a spot color reference step of converting a spot
color name into the coordinate values of the colorimetry
20 color space;

a proof condition conversion step associated with
a proof condition, of converting the coordinate values of
the colorimetry color space into coordinate values of the
second color space; and

25 a composition step of synthesizing, on the
colorimetry color space or the second color space, image
data defined by coordinate values of the colorimetry color

space or the second color space, wherein the process color image data is converted, with image data defined by coordinate values of the colorimetry color space or the second color space, wherein the spot color name is converted,

wherein the printing image data, which comprises the process color image data defined by the coordinate value of the first color space, and the spot color image data defined by the coordinate value of the characteristic direction, is converted into the image data defined by the coordinate value of the second color space, for the proofer.

2. A color conversion method according to claim 1, wherein said composition step is a step of synthesizing different types of image data on the second color space, of the printing image data, the process color image data defined by the coordinate value of the first color space is converted into image data defined by the coordinate values of the colorimetry color space in said printing condition conversion step, and the image data defined by the coordinate values of the colorimetry color space thus obtained through the conversion is further converted into image data defined by the coordinate value of the second color space in said proof condition conversion step,

the spot color name is converted into the coordinate values of the colorimetry color space in said

spot color reference step, and the coordinate values of the colorimetry color space thus obtained through the conversion is converted into the coordinate value of the second color space in said proof condition conversion step, and

in said composition step, the image data defined by the coordinate value of the second color space, for the proofer, is synthesized in accordance with the image data defined by the coordinate value of the second color space, after conversion by said proof condition conversion step, the coordinate value of the second color space corresponding to the spot color, after conversion by said proof condition conversion step, and the spot color image data of the printing image data.

3. A color conversion method according to claim 1, wherein said composition step is a step of synthesizing different types of image data on the colorimetry color space,

of the printing image data, the process color image data defined by the coordinate value of the first color space is converted into image data defined by the coordinate values of the colorimetry color space in said printing condition conversion step,

the spot color name is converted into the coordinate values of the colorimetry color space in said spot color reference step,

in said composition step, the image data defined by the coordinate values of the colorimetry color space, for the proofer, is synthesized in accordance with the image data defined by the coordinate values of the colorimetry color space, after the conversion by said printing condition conversion step, the coordinate values of the colorimetry color space corresponding to the spot color, after the conversion by said spot color reference step, and the spot color image data of the printing image data, and

the image data defined by the coordinate values of the colorimetry color space, for the proofer, which is synthesized by said composition step, is converted by said proof condition conversion step into the image data defined by the coordinate value of the second color space, for the proofer.

4. A color conversion method according to claim 2, wherein prior to conversion of the printing image data into the image data for the proofer, there is produced a process color conversion step in which the coordinate value of the first color space is directly converted into the coordinate value of the second color space in accordance with said printing condition conversion step and said proof condition conversion step,

in conversion of the process color image data of the printing image data, there is applied said process

color conversion step instead of individual application of both said printing condition conversion step and said proof condition conversion step, so that of the printing image data, the process color image data defined by the
5 coordinate value of the first color space is converted into image data defined by the coordinate value of the second color space before synthesized with the spot color image data.

10 5. A color conversion apparatus for converting printing image data, which comprises process color image data defined by a coordinate value of a predetermined first color space, and spot color image data defined by a coordinate value of a characteristic direction, into image
15 data defined by a coordinate value of a predetermined second color space, for a proofer for outputting a proof image in which an image obtained through printing of an image based on the printing image data in accordance with a predetermined printing condition is reproduced, said color
20 conversion apparatus comprising:

a definition storage section for storing
a first coordinates conversion definition
associated with a printing condition, defining an
association between the coordinate value of the first color
25 space and the coordinate values of a colorimetry color space which is device-nondependent,
a spot color and coordinates conversion definition

defining an association between a spot color name and the coordinate values of the colorimetry color space,

5 a second coordinates conversion definition defining an association between the coordinate values of the colorimetry color space and the coordinate value of the second color space, and

10 a coordinates composition definition defining an association among coordinate values of the colorimetry color space or the second color space, wherein the process color image data is converted, on the colorimetry color space or the second color space, coordinate values of the colorimetry color space or the second color space, wherein the spot color name is converted, and a set of coordinate values wherein said two types of coordinate values are synthesized; and

15 a color conversion section for converting the printing image data, which comprises the process color image data defined by the coordinate values of the first color space and the spot color image data defined by the coordinate values of the characteristic direction, into the image data defined by the coordinate value of the second color space, for the proofer, referring to said first coordinates conversion definition, said spot color and coordinates conversion definition, said second coordinates conversion definition, and said coordinates composition definition, which are stored in said definition storage section.

6. A color conversion apparatus according to claim 5, wherein said coordinates composition definition, which is stored in said definition storage section, defines an association between said two types of coordinate values of the second color space and said set of coordinate values, and said color conversion section comprises:

first conversion means for converting the process color image data defined by the coordinate value of the first color space, of the printing image data, into image data defined by the coordinate values of the colorimetry color space, referring to said first coordinates conversion definition;

second conversion means for converting the spot color name into the coordinate values of the colorimetry color space, referring to said spot color and coordinates conversion definition;

third conversion means for converting the image data defined by the coordinate values of the colorimetry color space, after conversion by said first conversion means, into image data defined by the coordinate value of the second color space, referring to said second coordinates conversion definition;

fourth conversion means for converting the coordinate values of the colorimetry color space, associated with the spot color, after conversion by said second conversion means, into the coordinate value of the

second color space, referring to said second coordinates conversion definition;

5 first composition means for synthesizing the image data defined by the coordinate value of the second color space, for the proofer, in accordance with the image data defined by the coordinate value of the second color space, after conversion by said third conversion means, the coordinate value of the second color space corresponding to the spot color, after conversion by said fourth conversion
10 means, and the spot color image data of the printing image data, referring to said coordinates composition definition.

7. A color conversion apparatus according to claim 5, wherein said coordinates composition definition, which is stored in said definition storage section, defines
15 an association between said two types of coordinate values of the colorimetry color space and said set of coordinate values, and said color conversion section comprises:

fifth conversion means for converting the process
20 color image data defined by the coordinate value of the first color space, of the printing image data, into image data defined by the coordinate values of the colorimetry color space, referring to said first coordinates conversion definition;

25 sixth conversion means for converting the spot color name into the coordinate values of the colorimetry color space, referring to said spot color and coordinates

conversion definition;

second composition means for synthesizing the image data defined by the coordinate values of the colorimetry color space, for the proofer, in accordance with the image data defined by the coordinate values of the colorimetry color space, after conversion by said fifth conversion means, the coordinate values of the colorimetry color space corresponding to the spot color, after conversion by said sixth conversion, and the spot color image data of the printing image data, referring to said coordinates composition definition; and

seventh conversion means for converting the image data defined by the coordinate values of the colorimetry color space, for the proofer, which is synthesized by said second composition means, into the image data defined by the coordinate value of the second color space, for the proofer, referring to said second coordinates conversion definition.

8. A color conversion apparatus according to claim 5, wherein said coordinates composition definition, which is stored in said definition storage section, defines an association between said two types of coordinate values of the colorimetry color space and said set of coordinate values, and said color conversion section comprises:

coordinates conversion definition construction means for constructing a third coordinates conversion

definition to directly associate the coordinate value of the first color space with the coordinate value of the second color space in accordance with said first coordinates conversion definition and said second coordinates conversion definition;

8 eighth conversion means for converting the process color image data defined by the coordinate value of the first color space, of the printing image data, into image data defined by the coordinate values of the second color space, referring to said third coordinates conversion definition;

10 ninth conversion means for converting the spot color name into the coordinate values of the colorimetry color space, referring to said spot color and coordinates conversion definition;

15 tenth conversion means for converting the coordinate values of the colorimetry color space corresponding to the spot color, after conversion by said ninth conversion means, into the coordinate value of the second color space, referring to said second coordinates conversion definition; and

20 third composition means for synthesizing the image data defined by the coordinate values of the second color space, for the proofer, in accordance with the image data defined by the coordinate values of the second color space, after conversion by said eighth conversion means, the coordinate values of the second color space corresponding

to the spot color, after conversion by said ninth conversion, and the spot color image data of the printing image data, referring to said coordinates composition definition.

5

9. A color conversion definition storage medium storing a color conversion definition for converting printing image data, which comprises process color image data defined by a coordinate value of a predetermined first color space, and spot color image data defined by a coordinate value of a characteristic direction, into image data defined by a coordinate value of a predetermined second color space, for a proofer for outputting a proof image in which an image obtained through printing of an image based on the printing image data in accordance with a predetermined printing condition is reproduced, said color conversion definition comprising:

a first coordinates conversion definition associated with a printing condition, defining an association between the coordinate value of the first color space and the coordinate values of a colorimetry color space which is device-nondependent;

a spot color and coordinates conversion definition defining an association between a spot color name and the coordinate values of the colorimetry color space;

a second coordinates conversion definition defining an association between the coordinate values of

the colorimetry color space and the coordinate value of the second color space, said second coordinates conversion definition being associated with a proof condition; and

- 5 a coordinates composition definition defining an association among coordinate values of the colorimetry color space or the second color space, wherein the process color image data is converted, on the colorimetry color space or the second color space, coordinate values of the colorimetry color space or the second color space, wherein
- 10 the spot color name is converted, and a set of coordinate values wherein said two types of coordinate values are synthesized.

ABSTRACT OF THE DISCLOSURE

Printing image data is converted into image data
for a proofer through a print condition conversion process
for converting CMYK for printing into L*a*b*, a spot
5 color reference process for converting a spot color name
into L*a*b*, a printer condition conversion process for
converting L*a*b* into RGB for proof, and a composition
process for synthesizing a process color with a spot color.

Fig.1




Fig.2




Fig.3




Fig.4




Fig.5



Fig.6




Fig.7




Fig.8




Fig.9




Fig. 10




Fig. 11




Fig. 12




Fig.13




Fig. 14





Fig.15



Declaration and Power of Attorney for Patent Application

特許出願宣言書及び委任状

Japanese Language Declaration

日本語宣言書

下記の氏名の発明者として、私は以下の通り宣言します。

As a below named inventor, I hereby declare that:

私の住所、私書箱、国籍は下記の私の氏名の後に記載された通りです。

My residence, post office address and citizenship are as stated next to my name,

下記の名称の発明に関して請求範囲に記載され、特許出願している発明内容について、私が最初かつ唯一の発明者(下記の氏名が一つの場合)もしくは最初かつ共同発明者であると(下記の名称が複数の場合)信じています。

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled

COLOR CONVERSION METHOD,

COLOR CONVERSION APPARATUS
AND COLOR CONVERSION DEFINITION STORAGE
MEDIUM

上記発明の明細書(下記の欄でX印がついていない場合は、本書に添付)は、

the specification of which is attached hereto unless the following box is checked:

☐ 月 日に提出され、米国出願番号または特許協定条約

☐ was filed on _____
as United States Application Number or
PCT International Application Number

国際出願番号を _____ とし、

(該当する場合) _____ に訂正されました。

_____ and was amended on
_____ (if applicable).

私は、特許請求範囲を含む上記訂正後の明細書を検討し、内容を理解していることをここに表明します。

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above.

私は、連邦規則法典第37編第1条56項に定義されるとおり、特許資格の有無について重要な情報を開示する義務があることを認めます。

I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations, Section 1.56.

Japanese Language Declaration

(日本語宣言書)

私は、米国法典第35編第119条(a)-(d)項又は第365条(b)項に基づき下記の、米国以外の国の少なくとも一カ国を指定している特許協力条約第365条(a)項に基づく国際出願、又は外国での特許出願もしくは発明者証の出願についての外国優先権をここに主張するとともに、優先権を主張している本出願の前に出願された特許または発明者証の外国出願を以下に、枠内をマークすることで、示しています。

Prior Foreign Applications

外国での先行出願

Hei, 11-259831
(Number)
(番号)

Japan
(Country)
(国名)

(Number)
(番号)

(Country)
(国名)

(Number)
(番号)

(Country)
(国名)

私は、第35編米国法典119条(e)項に基づいて下記の米国特許出願規定に記載された権利をここに主張致します。

(Application No.)
(出願番号)

(Filing Date)
(出願日)

私は、下記の米国法典第35編第120条に基づいて下記の米国特許出願に記載された権利、又は米国を指定している特許協力条約第365条(c)に基づく権利をここに主張します。又、本出願の各請求範囲の内容が米国法典第35編第112条第1項又は特許協力条約で規定された方法で先行する米国特許出願に開示されていない限り、その先行米国出願書提出日以降で本出願書の日本国内又は特許協力条約国際出願提出日までの期間中に入手された、連邦規則法典第37編第1条第56項で定義された特許資格の有無に関する重要な情報について開示義務があることを認識しています。

(Application No.)
(出願番号)

(Filing Date)
(出願日)

(Application No.)
(出願番号)

(Filing Date)
(出願日)

私は、私自身の知識に基づいて本宣言中で私が行う表明が真実であり、かつ私の入手した情報と私の信ずるところに基づき表明が全て真実であると信じていること、さらに故意になされた虚偽の表明及びそれと同等の行為は米国法典第1801条に基づき、罰金または拘禁、もしくはその両方により処罰されること、そしてそのような故意による虚偽の声明を行えば、出願した、又は既に許可された特許の有効性が失われることを認識し、よってここに上記のごとく宣誓を致します。

I hereby claim foreign priority under Title 35, United States Code, Section 119(a)-(d) or 365(b) of any foreign application(s) for patent or inventor's certificate, or 365(a) of any PCT International application which designated at least one country other than the United States, listed below and have also identified below, by checking the box, any foreign application for patent or inventor's certificate, or PCT International application having a filing date before that of the application on which priority is claimed.

14/September/1999
(Day/Month/Year Filed)
(出願年月日)

(Day/Month/Year Filed)
(出願年月日)

(Day/Month/Year Filed)
(出願年月日)

Priority Not Claimed

優先権主張なし

☐
☐
☐

I hereby claim the benefit under Title 35, United States Code, Section 119(e) of any United States provisional application(s) listed below.

(Application No.)
(出願番号)

(Filing Date)
(出願日)

I hereby claim the benefit of Title 35, United States Code Section 120 of any United States application(s), or 365(c) of any PCT International application designating the United States, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT International application in the manner provided by the first paragraph of Title 35, United States Code Section 112, I acknowledge the duty to disclose any material information which is material to patentability as defined in Title 37, Code of Federal Regulations, Section 1.56 which became available between the filing date of the prior application and the national or PCT International filing date of this application:

(Status: Patented, Pending, Abandoned)
(現況: 特許許可済、係属中、放棄済)

(Status: Patented, Pending, Abandoned)
(現況: 特許許可済、係属中、放棄済)

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Japanese Language Declaration

(日本語宣言書)

委任状: 私は、下記の発明者として、本出願に関する一切の手続きを米国特許商標局に対して遂行する弁理士又は代理人として、下記のことを指名致します。(弁理士、又は代理人の氏名及び登録番号を明記のこと)

POWER OF ATTORNEY: As a named inventor, I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and transact all business in the Patent and Trademark Office connected therewith (list name and registration number)

John H. Mion, Reg. No. 18,879; Thomas J. Macpeak, Reg. No. 19,292; Robert J. Seas, Jr., Reg. No. 21,092; Darryl Mexic, Reg. No. 23,063; Robert V. Sloan, Reg. No. 22,775; Peter D. Olexy, Reg. No. 24,513; J. Frank Osha, Reg. No. 24,625; Waddell A. Biggart, Reg. No. 24,861; Louis Gubinsky, Reg. No. 24,835; Neil B. Siegel, Reg. No. 25,200; David J. Cushing, Reg. No. 28,703; John R. Inge, Reg. No. 26,916; Joseph J. Ruch, Jr., Reg. No. 26,577; Sheldon I. Landsman, Reg. No. 25,430; Richard C. Turner, Reg. No. 29,710; Howard L. Bernstein, Reg. No. 25,665; Alan J. Kasper, Reg. No. 25,426; Kenneth J. Burchfiel, Reg. No. 31,333; Gordon Kit, Reg. No. 30,764; Susan J. Mack, Reg. No. 30,951; Frank L. Bernstein, Reg. No. 31,484; Mark Boland, Reg. No. 32,197; William H. Mandir, Reg. No. 32,156; Scott M. Daniels, Reg. No. 32,562; Brian W. Hannon, Reg. No. 32,778; Abraham J. Rosner, Reg. No. 33,276; Bruce E. Kramer, Reg. No. 33,725; Paul F. Neils, Reg. No. 33,102 and Brett S. Sylvester, Reg. No. 32,765

書類送付先:

Send Correspondence to:

SUGHRUE, MION, ZINN, MACPEAK & SEAS, PLLC
2100 Pennsylvania Avenue, N.W., Washington, D.C. 20037-3202

直通電話連絡先: (名称及び電話番号)

Direct Telephone Calls to: (name and telephone number)

(202)293-7060

唯一又は第一発明者名	Full name of sole or first inventor
発明者の署名	Eiji Teraue Date Sep. 4, 2000
住所	Residence Kanagawa, Japan
国籍	Citizenship JAPANESE
郵便の宛先	Post office address c/o FUJI PHOTO FILM CO., LTD., 798, Miyanodai, Kaisei-machi, Ashigarakami-gun, Kanagawa 258-8538 Japan
第二共同発明者名(該当する場合)	Full name of second joint inventor, if any
第二発明者の署名	Second inventor's signature Date
住所	Residence
国籍	Citizenship
郵便の宛先	Post office address

(第三以降の共同発明者についても同様に記載し、署名をする) (Supply similar information and signature for third and subsequent joint inventors.)